

## **LISTING OF THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**1. (Currently Amended)** A wiring device for use in a folding portable device including an upper unit, a lower unit and a hinge unit mechanically connecting said upper unit to said lower unit, said hinge unit having a rotating axis for rotating said upper unit in relation to said lower unit and a folding/unfolding axis perpendicular to the rotating axis for folding/unfolding said upper unit in relation to said lower unit, said wiring device comprising:

rotative direction wound portion having a first central axis corresponding to the rotating axis for being wound with a first part of a flexible printed cable which electrically connects said upper unit to said lower unit; ~~and~~

a folding/unfolding direction wound portion having a second central axis corresponding to the folding/unfolding axis for being wound with a second part of said flexible printed cable; and  
a cable fixing portion for fixing said flexible printed cable to said hinge unit.

**2. (Original)** A wiring device as claimed in Claim 1, wherein said rotative direction wound portion has a pair of winding guides for guiding said first part of said flexible printed cable; and wherein

said folding/unfolding direction wound portion has another pair of winding guides for guiding said second part of said flexible printed cable.

**3. (Original)** A wiring device as claimed in Claim 1, wherein said hinge unit has a folding/unfolding shaft with a thinner part thinner than the other part thereof to be used for said folding/unfolding direction wound portion.

**4. (Canceled)**

**5. (Currently Amended)** A wiring device as claimed in ~~Claim 4~~, Claim 1, wherein said cable fixing portion comprises:

a holding member for holding a third part of said flexible printed cable; and  
a fixing member for fixing said holding member to said hinge unit.

**6. (Original)** A wiring device as claimed in Claim 5, wherein said holding member keeps said third part of said flexible printed cable from coming in contact with a moving part of said hinge unit.

**7. (Original)** A wiring device for use in a folding portable device including an upper unit, a lower unit and a hinge unit mechanically connecting said upper unit to said lower unit, said hinge unit having a rotating axis for rotating said upper unit in relation to said lower unit and a folding/unfolding axis perpendicular to the rotating axis for folding/unfolding said upper unit in relation to said lower unit, said wiring device comprising:

a rotative direction wound portion having a first central axis corresponding to the rotating axis for being wound with a first part of a flexible printed cable which electrically connects said upper unit to said lower unit;

a folding/unfolding direction wound portion having a second central axis corresponding to the folding/unfolding axis for being wound with a second part of said flexible printed cable; and

a cable fixing portion for fixing a third part between said first part and said second part of said flexible printed cable.

**8. (Currently Amended)** A wiring device as claimed in Claim 7, wherein said hinge portion comprises a folding/unfolding shaft having a pair of end ~~portions~~portions; and wherein

said folding/unfolding direction wound portion is provided at each of said end portions of said folding/unfolding shaft.

**9. (Original)** A wiring device as claimed in Claim 8, further comprising said flexible printed cable, wherein

said second portion of said flexible printed cable is wound around said folding/unfolding direction wound portion at either of said end portions of said folding/unfolding shaft.

**10. (Original)** A wiring device as claimed in Claim 9, wherein said flexible printed cable has a spread shape so that said first part thereof is wound around said rotative direction wound portion, and that said second part thereof is wound around said folding/unfolding direction wound portion, and that said third part is extended from said rotative wound portion to said folding/unfolding direction wound portion through said cable fixing portion.

**11. (Original)** A wiring device as claimed in Claim 8, further comprising said flexible printed cable having a fourth part continuing from said third part thereof, wherein said second part of said flexible printed cable is wound around said folding/unfolding direction wound portion at one of said end portions of said folding/unfolding shaft while said fourth part of said flexible printed cable is wound around said folding/unfolding direction wound portion at the other of said end portions of said folding/unfolding shaft.

**12. (Original)** A wiring device as claimed in Claim 7, wherein said cable fixing portion comprises:

a holding member for holding said third part of said flexible printed cable; and  
a fixing member for fixing said holding member to said hinge unit.

**13. (Original)** A wiring device as claimed in Claim 12, wherein said cable holding portion has a T shape, and wherein  
said fixing member fixes said holding member to said hinge unit so that a horizontal bar of the T shape corresponds to the folding/unfolding axis and that a vertical bar of the T shape corresponds to the rotating axis.

**14. (Original)** A wiring device as claimed in Claim 7, wherein said rotative direction wound portion has a pair of winding guides for guiding said first part of said flexible printed cable; and

said folding/unfolding axis winding portion has another pair of winding guides for guiding said second part of said flexible printed cable.

**15. (Original)** A wiring device as claimed in Claim 7, wherein said hinge unit has a folding/unfolding shaft with a central axis corresponding to the folding/unfolding axis, said folding/unfolding shaft having a thinner part thinner than the other part thereof to be used for said folding/unfolding direction wound portion.

**16. (Currently Amended)** A wiring method for wiring a flexible printed cable between an upper unit and a lower unit of a folding portable device, said upper unit and said lower unit mechanically connected to each other by a hinge unit having a rotating axis for rotating said upper unit in relation to said lower unit and a folding/unfolding axis perpendicular to the rotating axis for folding/unfolding said upper unit in relation to said lower unit, comprising the steps of:

~~fixing a predetermined part of said flexible printed cable to said hinge unit;~~

winding a first winding part of said flexible printed cable around a rotative direction wound portion having a first central axis corresponding to the rotating axis; ~~and~~

winding a second winding part, of said flexible printed cable around a folding/unfolding direction wound portion having a second central axis corresponding to the folding/unfolding axis; and

fixing a predetermined part of said flexible printed cable that lies between the first and second winding parts to said hinge unit using a cable fixing portion suitable for attachment to the hinge unit.

**17. (Currently Amended)** A folding portable device including an upper unit, a lower unit and a hinge unit for mechanically connecting said upper unit to said lower unit, said hinge unit having a rotating axis for rotating said upper unit in relation to said lower unit and a folding/unfolding axis perpendicular to the rotating axis for folding/unfolding said upper unit in relation to said lower unit, said folding portable device comprising:

a flexible printed cable for electrically connecting said upper unit to said lower unit;  
a rotative direction wound portion having a first central axis corresponding to the rotating axis for being wound with a first part of said flexible printed cable around the rotating axis; and  
a folding/unfolding direction wound portion having a second central axis corresponding to the folding/unfolding axis for being wound with a second part of said flexible printed cable around the folding/unfolding axis; and  
a cable fixing portion for fixing said flexible printed cable to said hinge unit.

**18. (Original)** A wiring device as claimed in Claim 17, wherein said rotative direction wound portion has a pair of winding guides for guiding said first part of said flexible printed cable; and

said folding/unfolding direction wound portion has another pair of winding guides for guiding said second part of said flexible printed cable.

**19. (Original)** A wiring device as claimed in Claim 17, wherein said hinge unit has a folding/unfolding shaft with a thinner part thinner than the other part thereof to be used for said folding/unfolding axis winding portion.

**20. (Canceled)**

**21. (Currently Amended)** A wiring device as claimed in ~~Claim 20~~, Claim 17, wherein said cable fixing portion comprises:

a holding member for holding a third part of said flexible printed cable; and  
a fixing member for fixing said holding member to said hinge unit.

**22. (Original)** A wiring device as claimed in Claim 21, wherein said holding member keeps said third part of said flexible printed cable from coming in contact with a moving part of said hinge unit.